

# HD 955

9 wire • 136 column • 570 cps



Unbeatable  
performance and  
Unmatched  
reliability than  
ever before

- **Fastest Printing in Text & Graphics**
- **Long Print Head Life - 200 Million Characters**
- **Higher Reliability - 20,000 POH**
- **Dual Interface with Auto Interface Switching on Parallel & USB**
- **Excellent Copy Capability - Upto 1+ 5**
- **Higher Buffer Memory - 128 KB**

# HD 955 Product Specifications

Print Head - Type	9 Wire		
Print Width	136 Column @ 10 cpi		
Print Head Life	200 Million Characters*		
Ribbon Life*	3 Million Characters*		
Print Speed			
Character Pitch (cpi)	15	12	10
Super Speed Draft (cps)	-	570	-
High Speed Draft (cps)	-	507	507
Utility Draft (cps)	570	456	380
Near Letter Quality (cps)	143	97	95
Reliability - MTBF (Power on Hours)	20000 POH**		
Paper Slew	4.5 ips		
Copy Capability*	1+5 with carbon		
Consumables - Ribbon			
Fabric Type	Super High Density - Seamless		
Life**	3 million characters		
Throughput (ISO/IEC 10561)	335 pph		
Work Load	17000 pages per month		
Emulation	Epson FX, IBM Proprinter, OKI Microline		
First Printable Line	0.5 mm from top of page		
Fonts	Courier, HSD, Sans Serif, Gothic		
Utility Font Styles	Italics, Underline, Superscript, Subscript, Enhanced, Emphasised Double Width, Double Height		
Built-in Barcodes	Code 3 of 9, UPC A, UPC E, EAN 8, EAN 13, Interleaved 2 of 5, ZIP, Code 128		
Character Pitch	10, 12, 15, 17 & 20 cpi		
Standard Interface	Centronics Parallel & USB 1.1 Auto interface switching		

## Paper Specifications

Continuous Form Width	76 to 406 mm (3" to 16")
Cutsheet Thickness	183 to 363mm (7.2" to 14.3")

Graphics Resolution	Up to 240 x 216 dpi
---------------------	---------------------

Buffer Memory (Kilo Bytes)	128 KB
----------------------------	--------

Noise Level	Less than 56 dB(A)
-------------	--------------------

## Electrical Specifications

Operating Voltage	198 - 264V AC
Mains Frequency	50 / 60 Hz $\pm$ 2%
Power	58 W Operation, 10 W Idle

## Physical Dimensions

Size (WxDxH) mm	552 x 345 x 153
Weight (Kg)	9.5

## Ordering Information

Product Code	3006030003
--------------	------------

Description	HD 955
-------------	--------

Standard Configuration	CD-ROM containing online user manual and drivers Black Ribbon Parallel Interface Cable Power Cord
------------------------	--

Optional	Auto Sheet Feeder Bottom Push Tractor Top Pull Tractor RS232C Serial Interface Cable RS422A, 10/100 Base Tx network card (internal & external)
----------	--

## Consumables

2027070007	Super High Density Black Ribbon Cassette
1011030129	USB Cable

1 kg = 2.2lbs; 1 inch = 2.54 cms \* Max. possible copy capability \*\* @ 10 cpi draft # @ 33% print density and 25% duty cycle ## Excluding print head @ 33% print density and 25% duty cycle



Use only TVS-E "genuine for sure" consumables for your printers.



Seamless Ribbon



**EPA POLLUTION PREVENTER**  
As an Energy Star Partner TVS Electronics determines that this product meets the Energy Star Guidelines for energy efficiency.



Note: All specifications are at standard operating conditions and are subject to change without notice. All other products or brand names are registered trademarks of their respective holders.

TVS Electronics Limited  
34, Developed Plots, South Phase  
Industrial Estate, Guindy, Chennai 600 032, India.  
Ph: (44) 22325506/09/42005200.  
Fax: (44) 22327577  
**Visit us at [www.tvs-e.in](http://www.tvs-e.in)**

## Contact

**Taking IT to the heart of India**