

## HD 955 | REPORT PRINTER

Unbeatable performance and  
unmatched reliability



**Top printing speed -**  
570 cps



**Long print head life -** 200  
million characters



**High reliability -** 20,000  
POH MTBF



**Dual interface -** Parallel &  
USB with auto switching



**Higher copy capability -**  
1+5 copies

## Specifications

Print Method	: Serial impact dot matrix		
Print Direction	: Bi-directional logic seeking		
Print Head Type	: 9 wire		
Print Width	: 136 column @ 10 cpi		
Print Head Life	: 200 million characters*		
Print Speed	: 10	: 12	: 15
Super Speed Draft (cps)	: -	: 570	: -
High Speed Draft (cps)	: 507	: 507	: -
Utility (cps)	: 380	: 456	: 570
Letter Quality (cps)	: 95	: 97	: 143
Reliability - MTBF (Power on Hours)	: 20,000 POH**		
Paper Slew	: 4.5 ips		
Copy Capability*	: 1+5 with carbon		

### Consumables - Ribbon

Fabric Type	: Super high density - seamless		
Life**	: 3 million characters		
Throughput (ISO / IEC 10561)	: 335 pph		
Work Load	: 17,000 pages per month		
Emulation	: Epson FX, IBM Proprinter, OKI Microline		
First Printable Life	: 0.5 mm from top of page		
Fonts	: Courier, HSD, Sans Serif, Gothic		
Utility Fonts Styles	: Italics, Underline, Superscript, Subscript, Enhanced Emphasised, Double Width, Double Height		
Built-In Barcode Fonts	: Code 3 of 9, UPC A, UPC E, EAN8, EAN13, interleaved 2 of 5, ZIP, Code 128		
Character Pitch	: 10, 12, 15, 17 & 20 cpi		
Standard Interface	: Centronics Parallel & USB 1.1 Auto interface switching		

## Paper Specifications

Continuous Form Width	: 76 to 406 mm (3" to 16")
Cut Sheet Thickness	: 183 to 363 mm (7.2" to 14.3")
Graphic Resolution	: Up to 240 x 216 dpi
Buffer Memory (Kilo Bytes)	: 128 KB
Acoustics - Noise Level	: <56 dB (A)

## Software Specifications

Drivers	: Windows 95, 98, 98SE, 2000, Me, XP, NT 4.0, Linux Redhat
---------	--

## Electrical Specifications

Power Supply	: 198 - 264V AC
Mains Frequency	: 50 / 60 Hz (+ 2%)
Power	: 58 W operation, 10 W idle

## Environmental - Operating Conditions

Temperature	: +5° C to +45°C
Relative Humidity	: 10% to 80%

## Physical Dimensions

Size (W x D x H) mm	: 552 x 153 x 345
Weight	: 9.5 kg
Warranty	: 1 year

## Best suited for printing

Invoices | Ledgers | Accounts & Statements | Barcode printing

1 kg = 2.2 lbs; 1 inch = 2.54 cms

\*Max. possible copy capability

\*\*@ Draft 10 cpi

#@ 33% print density and 25% duty cycle

\*\* Excluding print head @ 33% print density and 25% duty cycle

\*\*\*. in lieu of USB

## CUSTOMER SEGMENTS



Transport Companies



Corporate Offices



Manufacturing Companies

## ORDERING INFORMATION

3006030003 HD 955

## OPTIONAL CONSUMABLES

2027070007 TVS-E RIBBON CASSETTE HD7XX/9XX

2023020004 TVS-E PRINT HEAD HD 955

## DEALER STAMP

### TVS ELECTRONICS LIMITED:

South Phase 7A, Second Floor,  
Industrial Estate, Guindy, Chennai - 600 032.

Call: 1800 200 5123 / 3030 9797 / 3030 7171 (prefix city STD code)

Visit: [www.tvse.in](http://www.tvse.in)