

# Print Labels Anywhere, Anytime

## LP 46 Dlite Label Printer



Compact and durable design



6" IPS printing speed



Interface: Standard USB port  
Optional: Ethernet, Serial,  
Bluetooth or Wifi



Increased storage  
Flash 16 MB & SDRAM 32 MB



High ribbon capacity of 300 M

Applications



Retail



Warehouse



Factory



Logistics

# Specifications



<b>Print method</b>	Thermal transfer
<b>Resolution</b>	203DPI
<b>Print width</b>	108mm(Max.)
<b>Print speed</b>	152mm/s(Max.)
<b>Memory</b>	SDRAM: 32MB, Flash:16MB (64MB optional)
<b>Sensor</b>	Photoelectric sensor
<b>TPH temperature detection</b>	Thermistor
<b>TPH position detection</b>	Microswitch
<b>Interface</b>	Standard USB port Optional: RS232 serial port, Ethernet, Bluetooth, WiFi (Bluetooth or WiFi)
<b>CPU</b>	32bit RISC MCP
<b>Barcodes</b>	ID: Code39,Code93,Codabar,Code128(Subsets A, B, and C), EAN-13,EAN-8,UPC-A,UPC-E,UPC/EAN Extensions, Planet Code, Standard 2 of 5,Industrial 2 of 5, Interleaved 2 of 5,LOGMARS, G51 Data Bar(RSS) 2D: PDF 417,MicroPDF417,QR Code,DataMatrix,MaxiCode, GSI Composite
<b>Character enlargement/rotation</b>	Rotate (0°, 90°, 180°, 270°) Enlarge (1-10x) Vector fonts support stepless scaling
<b>Character set</b>	Built in 7 dot matrix fonts and 1 vector font Support users to download dot matrix fonts and vector fonts
<b>Graphical</b>	Binary non-format bitmap, HEX, PCX, BMP and IMG can be download to FLASH, RAM
<b>Paper type</b>	Continuous paper, marking paper, label paper, perforated paper
<b>Paper width</b>	118mm (Max.)
<b>Paper roll OD (Max.)</b>	127mm(5 inch)
<b>Paper roll ID</b>	25.4mm(1 inch) /38mm(1.5 inch)
<b>Paper out</b>	Tear off/ Rewind/ Peel off (optional)/Cut (optional)
<b>Paper thickness</b>	0.06-0.25mm
<b>Ribbon length</b>	300m(Max.)
<b>Ribbon ID</b>	12.7mm/25.4mm
<b>Button, Indicators</b>	1 button,2 indicators
<b>Input</b>	100-240V AC, 50-60Hz
<b>Output</b>	24V DC, 2.5A
<b>Operation conditions</b>	5-45°C, 20 - 90%RH(40°C)
<b>Storage conditions</b>	-40-60°C, 20 - 93% RH(40°C)
<b>Dimensions</b>	280mm(L) x218mm(W)x180mm(H)
<b>Weight</b>	About 2.3kg

For trade enquiries contact

7550009339 / 9840460675 | sales-support@tvs-e.in

/TVSElectronics /tvs-electronics tvselectronics/