

# LP 46 Dlite Wifi

## Barcode & Label Printer



# PERFORMANCE WITH CONVENIENCE

Exclusive  
—for—  
AIDC



One Device to Fit All Interfaces  
USB + Serial + Ethernet + Wifi



More printing with a longer  
ribbon capacity of 300 M



Quicker labelling at a  
speed of 6 inches per second



Queue as many label jobs as possible,  
printing won't slow down  
Flash 64 MB & SDRAM 32 MB

### Applications



Shipping



Warehouse



Logistics



Factory




# Specifications



<b>Print method</b>	Thermal transfer
<b>Resolution</b>	203DPI
<b>Print width</b>	108mm(Max.)
<b>Print speed</b>	152mm/s(Max.)
<b>Memory</b>	SDRAM: 32MB, Flash: 64MB
<b>Print Head Life</b>	50 Km
<b>Sensor</b>	Photoelectric sensor
<b>TPH temperature detection</b>	Thermistor
<b>TPH position detection</b>	Microswitch
<b>Interface</b>	USB + Serial + Ethernet + Wifi
<b>CPU</b>	32bit RISC MCP
<b>Barcodes</b>	ID: Code39,Code93,Codabar,Code128(Subsets A, B, and C), EAN-13,EAN-8,UPC-A,UPC-E,UPC/C/EAN Extensions, Planet Code, Standard 2 of 5,Industrial 2 of 5, Interleaved 2 of 5,LOGMARS, G51 Data Bar(RSS) 2D: PDF 417,MicroPDF417,QR Code,DataMatrix,MaxiCode, GSI Composite
<b>Character enlargement/rotation</b>	Rotate (0°, 90°, 180°, 270°) Enlarge (1-10x)
<b>Character set</b>	Vector fonts support stepless scaling Built in 7 dot matrix fonts and 1 vector font
<b>Graphical</b>	Support users to download dot matrix fonts and vector fonts Binary non-format bitmap, HEX, PCX, BMP and IMG
<b>Paper type</b>	can be download to FLASH, RAM Continuous paper, marking paper, label paper, perforated paper
<b>Paper width</b>	118mm (Max.)
<b>Paper roll OD (Max.)</b>	127mm(5 inch)
<b>Paper roll ID</b>	25.4mm(1 inch) /38mm(1.5 inch)
<b>Paper out</b>	Tear off/ Rewind/ Peel off (optional)/Cut (optional)
<b>Paper thickness</b>	0.06-0.25mm
<b>Ribbon length</b>	300m(Max.)
<b>Ribbon ID</b>	12.7mm/25.4mm
<b>Button, Indicators</b>	1 button,2 indicators
<b>Input</b>	100-240V AC, 50-60Hz
<b>Output</b>	24V DC, 2.5A
<b>Operation conditions</b>	5-45°C, 20 - 90%RH(40°C)
<b>Storage conditions</b>	-40-60°C, 20 - 93% RH(40°C)
<b>Dimensions</b>	280mm(L) x218mm(VV)x180mm(H)
<b>Weight</b>	About 2.3kg

For trade enquiries contact

 7550009339 / 9840460675 |  sales-support@tvs-e.in

 /TVSElectronics  /tvs-electronics  tvselectronics/