

Features

- Bluetooth V4.2 Connectivity with auto-reconnect
- Direct plugin works without battery also
- Battery saver mode
- **BIS** Certified
- Rugged Design





















Restaurants



Juice Shops



Grocery Shops



Toll Gates







MP280 Specification	Features
Print Characteristics	
Print Method	Direct Thermal
Print Speed	up to 80 mm/s
Print Resolution	203 dpi
Print Width	Up to 48 mm
Sensor	Paper End: Reflective Sensor
	Paper Cover Open: Mechanical switch
Media Characteristics	
Media Type	Receipt
Media Width	58mm
Media Roll Diameter	Up to 40 mm
Media Thickness	60 to 100 μm
Supply Method	Easy Paper Loading
Physical Characteristics	·
Dimension	85 x 115 x 46 (W x D x H)
Weight	190 grams
Battery	7.4 V, Li-ion, 2100 mAh, Rechargeable
	Charging Time: Up to 2.10 hrs
Performance Characteristics	
Memory	32KB SDRAM, 256 KB Flash ROM, Ext
Interface Options	USB (CDC, HMSC), Bluetooth V4.2
Environment Characteristics	·
Operating Temperature	0 ~ 50°C, Humidity : 20 ~ 80% RH
Storage Temperature	0 ~ 60°C, Humidity : 10 ~ 90% RH
Software	
Emulation	Supports Standard ESC / POS Commands
SDK	Android SDK
Fonts / Graphics / Symbolizes	
Character Size	12x 24 dot font
Characters Per Line	24 characters/line 32 characters/line 42 characters/line
Character Sets	Alphanumeric: 95 Expanded Graphics:128 × 33 page
Graphics	Supporting graphics, formats, layouts, and logos
Barcode Symbolizes	EAN8, UPCA, CODE 39, CODE 128, ITF
Accessories	
Standard	Battery Pack & Power adopter
Optional	Printer External Art-leather Cover

TVS Electronics Limited

Arihant E-Park, 117/1, 8th & 9th Floor, L.B.Road, Chennai - 600 020 www.tvs-e.in | Email:sales-support@tvs-e.in

