

MSP 240 *Classic Plus*

9 wire ● 80 column ● 300 cps



The Faster Way
of Transacting

- Long Print Head Life - 200 Million Characters
- Wide Input Buffer - 100 KB
- Convertible Push / Pull Tractor
- Flexible Paper Handling - Top, Rear & Bottom
- Printer Built-in Barcode Font
- Ribbon Life - Up to 40 Million characters
- Wide Operating Voltage ~ 90 - 270V AC

MSP 240 *Classic Plus* Product Specifications

Print Method	Serial Impact Dot Matrix		
Print Direction	Bi-directional Logic Seeking		
Print Head - Type	9 Wire		
Print Width	80 Column		
Print Head Life	200 Million Characters*		
Print Speed			
Character Pitch (dpi)	15	12	10
High Speed Draft (cps)	375	-	-
Draft (cps)	-	300	250
Near Letter Quality (cps)	75	75	63
Resident Printer Fonts			
Draft	Draft		
Near Letter Quality	Roman, Sans Serif, Script		
Resident Barcode Font	Code 3 of 9		
Paper Handling			
Paper Path-Standard	Top, Rear and Bottom		
Continuous-Tractor Feed-Standard	Convertible Push & Pull		
Paper Size			
Continuous Form Width	3.5 - 10"		
Cutsheets Width	3.5 - 10"		
Paper Thickness (max) - Tractor feed	0.3mm		
Paper Thickness (max) - Friction feed	0.3mm		
Copy Capability*	1+3 with carbon		
Consumables - Ribbon			
Type	Unique TVS Ribbon Cassette with Replaceable Inkbank		
Colour	Standard Black		
Ribbon Life	40 Million Characters with 3 additional Inkbanks		
Cassette Refill Mode	Through Inkbank		
Inkbank Life	10 Million Characters**		
Input Buffer (Kilo Bytes)	100 KB		

Reliability-MTBF (Power on Hours)	10,000 POH **
Acoustics - Noise Level	55 dB(A)
Emulation	Epson ESC/P, IBM Proprinter
Interface Standard	Centronics IEEE-P1284A Parallel USB 2.0
Optional	RS 232C Serial
Electrical Specifications	
Operating Voltage	90 - 270V AC
Mains Frequency	47 - 63 Hz
Power (Standby)	12 W
Environmental - Operating Conditions	
Temperature	+5 to +45° C
Relative Humidity	10% to 80%
Physical Dimensions	
Size (WxDxH) mm	433 x 379 x 147
Weight (Kg)	5.7

Ordering Information

Product Code	3014070009
Description	MSP 240 Classic Plus
Standard Configuration	CD-ROM Quick Reference Manual Insertion Plate Convertible Push/Pull Tractor Black Ribbon Cassette + Inkbank Parallel Interface Cable USB Interface Cable Power Cord
Optional	RS232C Interface Kit (DB 25)
Consumables	
2028020001	TVS Ribbon Cassette 80 Column
2017100002	TVS Inkbank - Pack of 5

1 kg = 2.2lbs; 1 inch = 2.54 cms * Max. possible copy capability ** @ Draft 10 cpi # @ 33% print density and 25% duty cycle ## Excluding print head @ 33% print density and 25% duty cycle




Use only TVS-E "genuine for sure" consumables for your printers.



User replaceable Inkbank



10 Million Characters
TVS Ribbon Cassette



*Please prefix city STD code before dialing

Note: All specifications are at standard operating conditions and are subject to change without notice. All other products or brand names are registered trademarks of their respective holders.

Contact

TVS Electronics Limited
7/A Developed Plots, South Phase
Industrial Estate, Guindy, Chennai 600 032, India.
Ph: (44) 22325506/09/42005200.
Fax: (44) 22327577

Visit us at www.tvs-e.in

Taking IT to the heart of India