



MSP 240 STAR INVOICE PRINTER

The trade star













Printing Speed 375 cps -Faster printing



10,000 Power On Hours -Higher reliability



India's First Vertical Printer - Saves space



Wide Operating Voltage -Works in any condition, anywhere



Selicon Self-Lubrication Mechanism - Maintenance free. No more carriage stuck





The MSP 240 Star Advantage

The new 'Turbodot' print head from TVS-E is designed and precision engineered to obtain the best results.

Sealed coils enhances the thermo-cooling capacity of the print head

In comparison to the conventional tungsten pins, the HSS (High Speed Steel) pins used in 'Turbodot' print head ensures precise dot placement.

The exterior of the print head is designed with increased number of Heat Sink Fins for better heat dissipation. A special exterior coating on Heat Sink enhances heat dissipation.

The specially designed Plastic Front Profile guarantees smooth ribbon movement, thus slowing the wear and tear of the ribbon fabric and improving ribbon life.

Specifications

Print Method : Serial impact dot matrix Print Direction : Bi-directional logic seeking

Print Head Type : 9 wire Print Width : 80 column

Print Head Life : 200 million characters*

Positioning Speed : 375 cps

Print Speed

Character Pitch (cpi): 10 12 15 High Speed Draft 333 338 (cps) 300

Draft (cps) 250 375 Near Letter Quality / 75 75 63 LQ (cps)

Resident Printer Fonts

High Speed Draft : Standard 10 and 12 cpi

: Standard 10, 12, 15, 17 and 20 cpi Draft

Near Letter Quality : Roman, Sans Serif, Script

Resident Barcode : Code 3 of 9

Paper Handling

Paper Path - Standard: Top, rear and bottom

Continuous Tractor : Convertible push and pull paper size

Feed - Standard Paper Size

Continuous Form : 3.5 - 10"

Cut Sheet Width : 3.5 - 10" Paper Thickness : 0.3 mm

(max) - Tractor Feed

Paper Thickness : 0.3 mm (max) - Friction Feed

Copy Capability* : 1+3 with carbon Consumables - Ribbon

Type : Patented TVS-E ribbon cassette with user

replaceable Inkbank

: Jet black Colour

Ribbon Life : 40 million characters with 3 additional

Inkbanks Cassette Refill mode : Through Inkbank

: 10 million characters** Inkbank Life : 100 KB

Input Buffer (Kilo Bytes)

Reliability MTRE

: 10000 POH ** (Power on Hours)

Acoustics

: 55 dB (A)

(Noise Level)

Emulation : EPSON ESC / P, IBM Proprinter

Interface

Standard : As per the printer part number.

Software Specification.

Drivers : Windows 9X, NT 4.0, Me, 2000, 2003, XP,

Vista, Windows 7, Linux

Electronic Guide : HTML based

Electrical Specifications

Operating Voltage : 90V - 270 V AC : 47 - 63 Hz Mains Frequency Power (Standby) : ~12 W **Environmental - Operating Conditions** Temperature : +5° to +45°C Relative Humidity · 10% to 80%

Physical Dimensions

Size (W x D x H) mm : 433 x 379 x 147

Weight : 5.7 kg

Warranty 2 years including print head

(only valid on registration)

Best suited for printing

Bills | Receipts | Tickets | Coupons | Invoices | Statements

1 kg = 2.2lbs; 1inch = 2.54 cms

*Max. possible copy capability

"© Draft 10 cpi, "© 33% print density and 25% duty cycle
Excluding print head © 33% print density and 25% duty cycle

. in lieu of USB



TVS ELECTRONICS LIMITED:

South Phase 7A, Second Floor, Industrial Estate, Guindy, Chennai - 600 032.

Call: 1800 200 5123 / 3030 9797 (prefix city STD code)

Visit: www.tvs-e.in