






NO MORE WORRIES OF MULTIPLE WIRES.









DECLUTTER YOUR BILLING DESK.

PRESENTING MSP 270 STAR WITH BLUETOOTH CONNECTIVITY



-  Eliminate wires, except for printer power
-  Support BT 5.0
-  Vehicle mounted printing applications
-  Print directly from tablets and phones
-  Supports 10 meters distance

-  Printing Speed 270 CPS @ 10 CPI / 375 CPS @ 15 CPI
-  Reliability: 15000 Power On hours
-  Interfaces: Parallel/USB/BT5.0
-  Enhanced print head life
-  iSense - built-in self-diagnostic tool
-  Wide Operating Voltage: 90V -270V AC

Suitable for:



Retail



Pharmacy



Hospitality



Logistics

MSP 270 STAR

WITH BLUETOOTH CONNECTIVITY



Specification

Printing Technology

Print Method	Serial impact dot matrix
Number of Pins in Head	9 pins
Print Direction	Bi-directional
Control Code	ESC / P, IBM Proprinter
Print Width	80 Column
Print Head Life	200 Plus Million Characters
Printer Speed	320 CPS

Print Speed

High Speed Draft	10 / 12 / 15 cpi	350 / 360 / 400 cps
Draft	10 / 12 / 15 cpi	270 / 320 / 375 cps
NLQ	10 / 12 / 15	65 / 75 / 75 cps

Print Characteristics

Character Sets	
Resident Printer font	
Draft	Draft
Near Letter quality	Roman, Sans Serif, Script
Resident Barcode Fonts	Code 3 of 9

Printable Columns

Pitch	10 / 12 / 15 / 17 / 20 cpi
	80 / 96 / 120 / 137 / 160 cpl

Paper Handling

Paper Path Tractor / Manual	Top, rear and bottom
Continuous Tractor	Convertible push and pull
Cut Sheet (Single Sheet)	3.5 - 10"
Cut Sheet Width	3.5 - 10"
Paper Thickness	0.3 mm
Continuous Paper	3.5 - 10"
Roll Paper	

Paper Feeding

Standard	Friction, Push Tractor
Copies	1+3 with carbon
Line Spacing	"4.23mm (1/6") or programmable in increments of 0.118mm (1/216")"

Input Data Buffer Interface

100 KB
Bi-directional parallel (IEEE-1284 nibble mode supported)
USB 2.0 Full-Speed Serial (Optional)

Ribbon Cartridge

Standard	"Patented TVS-E ribbon cassette with user replaceable Ink bank
----------	--

Reliability

Mean Time Between Failure (MTBF)	15000 POH
Acoustics	55 dB (A) in ISO 7779 Sonic Pattern
Emulation	EPSON ESC/P, IBM Proprinter
Control Panel	4 switches and 5 LEDs

Environmental Conditions (Operating)

Temperature	(+5 C to +45C)
Humidity	10% to 80%

Electrical Specification

Rated Voltage	90V - 270V AC
Rated Frequency	47 - 63 Hz

Power Consumption

Operating	34W - Self test
Standard by	12 W

Printer Driver / Utility

Operating System	"Windows 9X, NT 4.0, ME, 2000, 2003, XP, VISTA, Windows 7, Linux"
Electronic Guide	HTML Based

Dimesions

Size (W D H) mm	433 X379 X147 mm
Weight	5.7 kg

Warranty

1 year

For trade enquiries contact

☎ 7550009339 / 9840460675 | ✉ sales-support@tvs-e.in

📘 /TVSElectronics 🌐 /tvs-electronics 📷 /tvselectronics