



The upgrade my store needed!
- Rahul, Dept. Store owner



A star that keeps pace with my business.
- Anu, Pharmacy owner

Presenting
MSP 270 Star
Dot Matrix Printer
9 wire | 80 Column | 320 CPS



Suitable for:



Retail



Pharmacy



Hospitality

MSP 270 Star

Specification

Printing Technology Print Method Serial impact dot matrix Number of Pins in Head 9 pins Print Direction Bi-directional Control Code ESC / P, IBM Proprinter Print Width 80 Column Print Head Life 200 Plus Million Characters Printe Speed 320 CPS		Input Data Buffer 100 KB Interface Bi-directional parallel (IEEE-1284 nibble mode supported) USB 2.0 Full-Speed Serial	
Print Speed High Speed Draft 10 / 12 / 15 cpi 350/ 360 / 400 cps Draft 10 / 12 / 15 cpi 270 / 320 / 375 cps NLQ 10 / 12 / 15 65 / 75 / 75 cps		Ribbon Cartridge Standard "Patented TVS-E ribbon cassette with user	
Print Characteristics Character Sets Resident Printer font Draft Draft Near Letter quality Roman, Sans Serif, Script Resident Barcode Fonts Code 3 of 9		Reliability Mean Time Between Failure (MTBF) 15000 POH Acoustics 55 dB (A) in ISO 7779 Sonic Pattern Emulation EPSON ESC/P, IBM Proprinter Control Panel Interface 4 switches and 5 LEDs USB/Parallel (optional Serial)	
Printable Columns Pitch 10 / 12 / 15 / 17 / 20 cpi 80 / 96 / 120 / 137 / 160 cpl		Environmental Conditions (Operating) Temperature (+5 C to +45C) Humidity 10% to 80%	
Paper Handling Paper Path Tractor / Manual Top, rear and bottom Continuous Tractor Convertible push and pull Cut Sheet (Single Sheet) 3.5 - 10" Cut Sheet Width 3.5 - 10" Paper Thickness 0.3 mm Continuous Paper 3.5 - 10" Roll Paper		Electrical Specification Rated Voltage 90V - 270V AC Rated Frequency 47 - 63 Hz	
Paper Feeding Standard Friction, Push Tractor Copies 1+3 with carbon Line Spacing "4.23mm (1/6") or programmable in increments of 0.118mm (1/216")"		Power Consumption Operating 34W - Self test Standard by 12 W	
		Printer Driver / Utility Operating System "Windows 9X, NT 4.0, ME, 2000, 2003, XP, VISTA, Windows 7, Linux" Electronic Guide HTML Based	
		Dimesions Size (W D H) mm 433 X379 X147 mm Weight 5.7 kg	
		Warranty 1 year	