


# Designed With Higher Expertise

## RP 3230




Compact and  
Ergonomically Designed



Print speed upto 230mm/s  
with minimal noise



Type-B USB 2.0, Ethernet,  
RS232, Cash drawer



Support  
wall mounting



Three at-a-glance LEDs for  
visualizing printer status



Support error  
reprint

Compatible  
with



### Applications



Retail



Restaurant



Logistics



Manufacturing



Medical Care

# Specifications



Print Method	Direct thermal printing
Resolution	203 DPI (8dots/mm)
Print Width	72mm / 48mm
Print Speed	Max. 230mm/s
Emulation	ESC/POS
Page Mode	Support
Paper Type	Thermal continuous paper
Paper Width	79.5±0.5mm/57.5±0.5mm
Paper Container	Max. 83mm
Paper Feed	Upward feed direction
Standard	USB Type-B, Ethernet, Serial, Cash drawer
Optional	USB+WiFi+BT
1D barcode	UPC-A, UPC-E, Code 39, Code 93, Code128, EAN8, EAN13, Interleaved2 of 5,Codabar
2D barcode	QR Code,PDF417
Chinese Character	Simplified/Traditional: (24 x 24 dots)
English Character	ASCII: Font A 12×24, Font B 9×17
Code Page	47
Graphics	Support bitmap printing and bitmap downloading with different density and user defined (Max. 64K for each bitmap and the total bitmap cannot exceed 512K)
Buzzer	Internal buzzer kitchen bell(optional)
Sensor (Standard)	Paper end, cover opening, cutter jam, TPH over-temperature
Sensor (Optional)	Black mark sensor
RAM	4 MB
Flash	4 MB
Input Power	AC100V-240V, 50/60Hz
Output Power	DC 24V 2A
Driver	Windows 7/8/10, Windows Server 2008/2012/2016 Linux, Javapos,OPOS,MacOS
Utility Tool	Windows 7/8/10, Windows Server 2008/2012/2016
TPH Life	100 km
Cutter Life	1,500,000 times
Operating	0~45°C / 5~95%RH No condensation
Storage	-20~70°C / 15~95%RH No condensation
Certification	BIS
Weight	0.916kg
Dimension	140x 179 x117(LxWxH (mm))

For trade enquiries contact

☎ 7550009339 / 9840460675 | ✉ sales-support@tvs-e.in

📘 /TVSElectronics 🌐 /tvs-electronics 📷 tvselectronics/